
PROPANE ACCESSORIES

## PROPANE ACCESSORIES

**FLARE FITTINGS** 






# **Adapter Nut**

**QCC Type 1 Connection** Male Female Conn - RH Item No. Outlet

**G1851-A02** 1/4" NPT 1-5/16" Acme Connects the grill regulator to Type 1 valves shown.

Provides 110,000 btu/hr excess flow protection & thermal shutoff protection for grill cylinders. After closure, bypass flow is only 10 CFH at 100 psi inlet pressure. The thermal shutoff occurs when the temperature of the plastic coupling reaches 240°F to 300°F and the material softens, allowing the check valve to close off the flow.



# Coupling, Plug

5LPA-9 \$6.65 EA 5LPA-9 Plug (use only with Sturgis quick-disconnect) 5LPA-10 C Plug (use only with Hansen quick-disconnect) Make quick-disconnect plug by 1/4" M NPT. Connects the grill regulator to a 3329LGQ4.0 quick-disconnect cylinder valve.

5LPA-10C \$12.00 EA

# High Pressure Hose Assemblies

## LP-Gas UL Listed Small Hose Assemblies

3/8" M NPT x 3/8" F Flare 1/4" ID Hose ITEM **LENGTH** 

42410-24 24" \$9.97 EA 42410-36 36" \$12.31 EA 42410-48 48" \$14.71 EA

3/8" ID Hose

42610-24 24" \$11.71 EA 42610-36 36" \$14.80 EA 48" \$17.48 EA 42610-48

3/8" F Flare x 3/8" F Flare 1/4" ID Hose

ITEM	LENGT	H
42413-24	24"	\$10.14 EA
42413-36	36"	\$12.45 EA
42413-48	48"	\$14.65 EA
42413-60	60"	\$16.97 EA

#### 3/8" ID Hose

\$12.54 EA	24"	42613-24
\$15.34 EA	36"	42613-36
\$17.57 EA	48"	42613-48
\$20.80EA	60"	42613-60

## LP-GAS ENGINE FUEL HOSE



### F276334 Quick-Disconnect Adapter for Standard POL valves

Male POL by quick-disconnect coupler. Converts standard POL cylinder valve to Type 2 quick-disconnect valve. Takes the 5LPA-9 or 5LPA-10C PLUG

\$32.50 EA

Swivel Male POL

## Filling Adaptor for Type 2 quickdisconnect couplers

Female POL by plug nipple for filling into the 5LPN quick disconnect coupling for grills. Does not include a check valve in outlet.

**5LPA-FP** \$8.50 EA

**CONSTRUCTION:** Specifically compounded heat resistant synthetic rubber seamless inner tube. Single braid of stainless steel wire. The hose is impregnated with oil and

More hoses in Oxy-Fuel **Accessories Section** 

mildew-resistant rubber compound. APPLICATION: For LP-Gas engine fuel lines.

HOSE ID HOSE OD MINIMUM

TEMPERATURE RATING: -40° TO +257° F Inner tube specifically compounded to resist temperatures

WORKING

PRICE			
PER FOOT			
10' PER SIZE			
MINIMUM			

ITEM 20820-4-4

20820-6

20820

20420

20420-6

20120-6

27920-6

27920-8

27720-6

27720-8

20120-6-6

20820-8-8

20820-8-10

<b>MINIMUM</b> ITEM (IN) (IN) BURST (PSI) PR	ESSURE (FSI
\$5.42 EA \$\$25UL-4 3/16" .52 1750 \$5.57 EA \$\$25UL-6 5/16" .68 1750	350 350
<b>\$5.64 EA SS25UL-8</b> 13/32" .77 1750	350
<b>\$6.78 EA SS25UL-10</b> 1/2" .92 1750	350

COUPLINGS FOR SS25UL HOSE

HOSE ID

3/16"

5/16"

1/2"

1/2"

1/2"

5/16"

5/16"

5/16"

5/16

5/16"

## **Reserve Gas Adaptors**

"O" ring nose

\$8.50 EA

G487 \$11.50 EA

1/4" NPT



G1638

G487 1"-20 F x F POL Allows you to connect a disposable cylinder to a regulator that has a POL inlet, providing a reserve gas supply to outdoor grill, etc.

TYPE 3

CONNECTION

## LIFT TRUCK SAFETY

#### CHECK CONNECTORS

MALE LIFT TRUCK CONNECTOR 1-1/4" Acme x 3/8" F. NPT. Internal check mechanism is easily replaceable. Connector Part No. 1428M is interchangeable with Rego 7141M and Fisher M220M.

\$22.14 EA For same fitting W/Female - 1-1/4" Acme Thread. #1428F \$22.14 EA

## The Original Mr. Heater Series

#### "Mr. Heater" - Original Mr. Heater Series

Variable Output Of 8, 12 & 14,000 BTU/Hr.

Hi/Medium/Low Regulator

Safety Shutoff Soft Nose P.O.L.

For Direct Connection To 4-20 lb. Bulk Cylinder


#### Features & Uses Of Infra-Red Heaters

Efficient, fast heat, economical, convenient, quiet, durable, minimal maintenance, full 1-year warranty. Typical uses: Patios, workshops, sheds, poolside areas, large open sided tents, animal stalls, vehicle maintenance, outdoor jobs

Portable Infra-Red Heaters Are Designed For Outdoor Use Only. Cylinders Not Included.



**#PLUG-B \$1.25 EA** 





1-1/4" #1875-3A \$3.75 EA

1-3/4" #1850-10 (W / STRAP) \$7.95 EA



26Condensed Catalog