ARC TYPE STUD SYSTEMS - CONTROLLER w/GUN - STUD WELDING SYSTEM

Burco ST-16 Drawn Arc Stud Welder Controller

(Requires a Welding DC Power Source)



Weldable stud range 1/4" – 3/4"



- Allows connection of stud welding guns to most constant current (cc) welding power supplies.
- Drawn arc stud welding using ceramic ferrules.
- Sate-of-the-art microprocessor controls for reproducible welding results.
- Small and lightweight.
- Easily serviced.
- With dual voltage capacity: either 110 V or 230 V can be selected.

BURCO ST-16 Timer/Controller Package, *Complete Part # 50F21 \$5,295.00 EA

Includes:

Controller unit #50F51 \$4,466.70 EA
Stud Gun, Part (see next page)
Interconnect cable package #45F60 \$249.00 EA

Input voltage 110 / 208 / 230 V, 1 phase

Maximum input current (DC) 1500 amps
Weldable stud range 1/4" 3/4" diameter
Time adjustment range 150-1500 MS
DC Voltage range 60-100

Dimensions 16" X 10" X 11.5"

Weight 35 lbs.

*Ferrule Grips & Chuck not included

Burco 802ELOTOP DRAWN ARC & Short Cycle Stud Wolder

Short Cycle Stud Welder



3/8" CAPACITY: - 1/2" PD-MAX.

- State-of-the-art stud welding power unit with fully controlled thyristor bridge; solid state current switching and timing
- Microcomputer controlled
- Eliminates separate controller packages
- Versatile with plenty of reserve power--cable lengths can be extended to over 100 ft.
- Harmonized static and dynamic properties provide excellent and consistent welding results
- Process variations:
 - 1. Stud welding with ceramic ferrule
 - 2. Short-cycle stud welding without ceramic ferrule. Requires Inert gas stud welding (optional)
- Small and lightweight for easy transport
- Self diagnosis (fault) circuits
- Safety switch off circuit
- One year warranty

Maximum output 800 AMP Rated output (3% duty cycle) 750 amps

Input voltage 230V / 400V / 460V; 50 / 60 Hz

Recommended input fuse size 35 / 25 amps

Weldable stud range Thin gauge to 1/2" diameter

Output current range 100-750 amps
Time adjustment range 10-120; 10-800MS
Dimensions: 20.5" L, 12.5" W, 13.8" H

Weight 109 lbs. (45 kg)



- O Power control unit (800 amps) Part # 55F08 (Call for Price)
- O K-22 Stud Gun w/16' cable leads Part # 42K22 (see next page for price)
- Cable package with 15' work cable and 2 clamps Part # 45F59 (see next page for price)

Optional Accessories – (see next page for price)

- O Inert gas control kit Part # 41F68
- Extension gun cable assembly, 25' Part # 50F07
- A variety of other guns

*Ferrule Grips & Chuck not included

K-22 Stud Gun