

from twisting, if you hit an obstacle, they make for exceptionally safe tools.

— 120V Electric Power Tools — Hammer Drills

Double Insulated with Auto-Stop Carbon Brushes



To implement 'CODE!' System requires purchase of accessory Code Key. For details see next page

Model # Order # Price Ea.	SBE560 00559 \$129.43	SBE660 00661 \$223.20	SBE750 00760 \$257.30	SBE1010 Plus 01008 \$420.83					
					Aluminum die-cast gear housing	-	Yes	Yes	Yes
					2-speed gear-box	-	Yes	Yes	Yes
Electronic gentle start feature	-	-	-	Yes					
Variable speed controlled by adjusting dial	Yes	-	-	Yes					
Current interruption protection	-	-	-	Yes					
Reversing facility	Yes	Yes	Yes	Yes					
Chuck	1/2" Geared	1/2" Geared	1/2" Geared	1/2" Keyless					
Metabo slip clutch	-	Yes	Yes	Yes					
Auto-stop carbon brushes	Yes	Yes	Yes	Yes					
Winding protection grid	-	Yes	Yes	Yes					
Thermal overload protection	-	-	-	Yes					
Maximum Tightening Torque	40 inch lbs.	142 inch lbs.	159 inch lbs.	248 inch lbs.					
Capacity - in concrete	1/2"	5/8"	3/4"	3/4"					
Capacity - in mild steel	3/8"	1/2"	1/2"	5/8"					
Capacity - in softwood	3/4"	1 3/16"	1 1/2"	1 1/2"					
No-load speed (RPM)	0-2800	0-1000/0-3000	0-1000/0-3000	0-900/0-2600					
No-load blows per minute (BPM)	0-50000	0-57000	0-57000	0-50000					
Amps	4.5	5.8	6.2	8.0					
Rated input watts	560	660	750	1010					
Chuck capacity	1/2"	1/2"	1/2"	1/2"					
Spindle thread	1/2 x 20 UNF	1/2 x 20 UNF	1/2 x 20 UNF	1/2" x 20 UNF					
Tool weight	5.3 lbs.	5.9 lbs.	6.6 lbs.	6.9 lbs.					
Shipping weight	7 lbs.	10.1 lbs.	10.8 lbs.	11.1 lbs.					
Length	10 3/4"	13"	13 3/8"	13 3/8"					
Carrying case	23882 (optional)	34445236 (standard)	34445236 (standard)	34445236 (standard)					
Standard Equipment:	1/2" chuck (35250)	1/2" chuck (35250)	1/2" chuck (35250)	1/2" chuck (36226)					
	Side handle (31052)	Side handle (31052)	Side handle (31052)	Side handle (31400077)					
	Depth gauge (27288)	Depth gauge (27288)	Depth gauge (27288)	Depth gauge (27288)					
	Chuck key (35167)	Chuck key (35167)	Chuck key (35167)	-					