## Heavy-Duty 3/8" (10mm) Right Angle Drill, 120V AC

#### Features:

- 100% ball-bearing construction provides durability and longer tool life
- Compact right-angle design for easy access in tight places
- Paddle switch is ideal for use in awkward positions and limited access areas
- Shielded chuck protects user and improves grip in confined areas
- Double gear reduction increases torque performance and decreases gear stress



Chuck Size	3/8 "
No Load Speed	1,200 rpm
Amps	3.2 Amps
Max Watts Out	200 W
Clutch	No
Capacity In Wood (Spade Bit)	1-1/8 "
Gear Reduction	Double
Capacity In Wood (Self-Feed)	N/A "
Capacity In Wood (Hole Saw)	1-1/8 "
Capacity In Wood (Auger Bit)	N/A "
Capacity In Steel (Twist Bit)	3/8 "
Capacity In Steel (Hole Saw)	3/4 "
Tool Weight	3.75 lbs
Shipping Weight	4.5 lbs











### Heavy-Duty 4-1/2" (115mm) Small Angle Grinder - DW402 Includes: **120V AC**

#### Features:

- 7.5 Amp AC/DC, 10,000 rpm motor provides high power, overload protection and speed for 4-1/2 grinding applications
- Metal gear case dissipates heat for longer bearing, gear and motor life
- Convenient paddle switch with lock-on button for easier gripping
- 3 position removable side handle for greater comfort and control
- AC/DC capacity works off welding machines and generators for increased productivity and versatility
- Spindle lock for quick and easy wheel changes
- Matched wheel flanges allow for use of common accessories



o clamp nut\* o guard o 3 position side handle 7.5 AC/DC Amps 10,000 rpm Use Wheels RPM Above Spindle Lock Yes

Diamond

Blade Guard

\$70.00 Ea

Only #DW4705

Diamond

#DW4706

\$3.60 Ea

Wheel Flange

10.33

4.5 lbs

Type 1

Cutting

Wheels

(7/8" hole) see pages 407

& 408

o grinding wheel

o backing flange\*

o wrench

Price \$105.80











\*Included with DW402 Grinder Backing Flange Dewalt Only\* DWBF \$3.44 Ea.

# DW402 (4-1/2") Accessory Options



Depressed Center, Grinding or Cutting Wheel – see pages 411 & 412



Surface Preparation Wheel see page 419



Flap (Sanding) Disc see page 416



Hubbed





4-1/2"Rubber Backing Pad see page 418



Abrasive (Sanding) Disc (7/8" hole) - see page 418



Center Nut 5/8-11 thread (sold with Rubber backing Pad)

Wire Cup Brush (2-3/4 or 3" ø, 5/8-11 thread) see page 438 (Type 1 Disc Guard) Dewalt



Wire (Stringer Bead) Knot Wheels (4" ø, 5/8-11 thread)



**Diamond Blades** 



Tuck Point 4" (mortar removal), #DW4710 \$45.50 Ea

Clamp (Locking) Nut 5/8-11 thread Dewalt Only.\* #5140001-90 \$4.25 Ea.

# Portable - Heavy-Duty 12" (1" arbor hole) Cut-Off Machine - D28754

### Features:

- 15.0 Amp/5.3 HP (maximum motor HP) motor provides high power and speed for metal and concrete cutting
- Epoxy coated field and armature provide long service life against abrasion from debris Adjustable guard for different cutting depths mounted at two points to maintain proper
- alignment Rotation directs sparks and debris towards the front of the tool and helps prevent climbing in the cut
- Dust sealed switch protects against dust ingestion for longer switch life
- Automatic turn-off brushes shut down the tool when brushes need to be changed to avoid tool damage
- 2 wire double insulated 'S' jacket rubber cord provides increased durability and life in hot and cold climates
- Spindle lock button for fast, easy wheel changing



Part No. D28754 Price \$668.80

**120V AC** 

Amps	15.0 Amps
Max Capacity (Round)	4-3/4 "
Tool Length	23.9 "
Tool Weight	15.0 lbs