120VAC Bench Grinders – Portable Grinders – Impact Wrench



Heavy-Duty 6" & 8" Bench Grinders

- Powerful induction motor for heavy-duty grinding operations
- Cast iron base and motor housing provide durability and prolong life
- Precision-machined aluminum tool rests allow the user to accurately position work
- Rear exhaust ports in wheel guards for smoother operation
- 12-1/2" distance between wheels for longer and larger grinding applications

Part No.	DW756	DW758
Price Ea	\$216.93	\$279.00
Amps	4.0 AC Amps	4.2 AC Amps
Horsepower	5/8 HP	3/4 HP
No Load Speed	3,450 rpm	3,600 rpm
Wheel Diameter	6 "	8 "
Spindle Diameter	1/2 "	5/8 "
Adjustable Tool Resets	Yes	Yes
Tool Length	15 "	16 "
Tool Weight	28.5 lbs	39.5 lbs

Accessories

For Bench grinding Wheels See page 415, Flap Wheels page 416& Wire Wheels pages 437 & 438

Includes:

- 36 grit wheel √ 60 arit wheel
- ✓ eye shields
- ✓ spark deflectors
- √ tool rests
 - ✓ adjusting wrench

Multitool

THE ULTIMATE FINISHING TOO

Convert Your Bench Grinder

MT36TG Part # Belt Size (in) 2" x 36" Disk Size 7" Table Size (in) 4-1/4" x 10" 15 lbs Net weight (lbs)

Attaches easily to most 6" / 7" / 8" Bench Grinders with minimum 1/3 H.P.

INCLUDES: 1EACH 3M BELT (100 GRIT) & PSA DISC (80 GRIT)

Multitool Sanding Belt and Disc Attachment w/ MITER TABLE & GUARD

MT36TG \$225.00 EA

Disc Size '7" Belt Size 36" x 2" **GRINDER NOT INCLUDED**

OSHA & UL COMPLIANT



6 in. Diameter Straight Grinder, 15 Amp, 5500 RPM



Includes

- ✓ Grinding Wheel
- ✓ Wheel Guard
- √ 1-1/16 in. Wrench
- ✓ Spanner Wrench

Features:

- 5500 rpm, 15 amp
- . 6 in, diameter wheel
- · Coated spindle housing for cool gripping surface
- Hinged face plate for quick easy wheel replacement

Accessories

For Bench grinding Wheels See page 415, Flap Wheels page 416 & Wire Wheels pages 436 & 437

A coated spindle housing make this heavy duty, Milwaukee Straight Grinder comfortable to hold on to while delivering an extra heavy duty 15 amps of power and 5500 RPM. Equipped with a hinged face plate with wing nut fasteners for easy wheel changes, this tool can accept up to 6 inch resinoid bond wheels. Wire brushes can also be attached for cleaning rust from work surfaces, as well as buffing wheels for polishing. An impact absorbing tool rest is provided so that the tool can be set down safely as the wheel coasts to a stop. The spindle is 5/8 inch for use with industry standard accessories for the rated diameter capacity.



1/2 IN. IMPACT WRENCH WITH ROCKER SWITCH AND DETENT PIN SOCKET RETENTION

Delivering 300 ft. lbs. of torque and weighing only 6 pounds, this tool has a great power to weight ratio. The powerful 7.0 amp motor drives a unique impact mechanism at 1800 RPM (no load). This model features a pin-detent system to securely retain sockets or adapters and a rocker switch for quick selection of forward or reverse. The ergonomically shaped handle with a soft cushioned grip provides a well-balanced and controllable feel to the tool. The special mechanism achieves desired installation torque faster and loosens rusted or fretted bolts in less time.

SPECIFICATIONS

Voltage 120 AC/DC 1/2 in. Square Drive Size Torque 300 ft.-lbs. No Load Speed 1,800 RPM **Amps** 7.0 No Load BPM 2.600 Cord Type 8 ft. Fixed Switch Type Rocker Soft Grip Handle Yes Flat End Detent Pin

Socket Retention Length 11-5/8 in. Tool Weight 6.0 lbs. Shipping Weight 7.6 lbs.




1/2" SQUARE DRIVE HEX SOCKETS

 Size	Part Number	Price
1/2"	49-66-3080	\$4.05 Ea
9/16"	49-66-3090	\$4.05 Ea
9/16"	49-66-3100	\$4.05 Ea
9/16"	49-66-3110	\$4.50 Ea
 9/16"	49-66-3120	\$4.50 Ea
 9/16"	49-66-3130	\$5.40 Ea

1/2" SQUARE DRIVE UNIVERSAL JOINT

Fits 1/2" Square Drive and used with Hex Sockets to reach difficult places at various angles...also allows clearance around obstructions



5" LENGTH 1/2" SQUARE DRIVE EXTENSION Adapts to 1/2" Square Drive. Provides 5"

additional length where required for use with

