## INTERSTATE

STANDARD BLOW GUNS

INTERSTATE Standard Series Blow Guns do not include a bypass or restrictors to limit output pressure. These blow guns should be used with a maximum inlet pressure of 30 PSI. All INTERSTATE Blow Guns have a 1/4" NPT Female inlet and a 1/8" NPT Female outlet.



B300 Standard Gun Without Tip - Basic Blow Gun Body





B301 Standard Gun With Brass Tip - Basic General Purpose Blow Gun






B302 Standard Gun With Rubber Tip - Ideal for applications where a metal tip could damage work

## **INTERSTATE**

**SAFETY BLOW GUNS** INTERSTATE Safety Series Blow Guns comply with \* OSHA 1910.242b and 1910.95 by using a tip that reduces the inlet pressure from a maximum of 150

PSI to an outlet pressure of 30 PSI at the nozzle. The tip also includes a safety by-pass which prevents excess pressure build-up in the gun if the nozzle becomes clogged or "dead-ended." All INTERSTATE Safety Series Blow Guns have a 1/4" NPT Female inlet and 1/8" Female outlet.



INTERSTATE Button Valves feature solid brass construction, and Buna-N (Nitrile) seals. Normal valve position is closed. Ideal for air and liquid lines operating at up to 175 PSI working pressure.



**BUTTON VALVES** 

Inlet Thread 1/4" NPTF

**Outlet Thread** 1/4" NPTF

Model No.


INTERSTATE Ball Valves feature forged brass bodies to provide extended service life and resistance to damage caused by extreme temperature applications. Inert Teflon seats and seals provide excellent corrosion resistance. Large handle allows more leverage for easy on/off operation.



WORKING PRESSURE 600 PSI W.O.G.

**BALL VALVES** 

Inlet Thread	Outlet Thread	Price	Model No
1/4" NPTF	1/4" NPTF	\$17.14 EA	VB04
3/8" NPTF	3/8" NPTF	\$17.14 EA	VB06
1/2" NPTF	1/2" NPTF	\$17.14 EA	VB08
3/4" NPTF	3/4" NPTF	\$27.90 EA	VB12
1" NPTF	1" NPTF	\$34.48 EA	VB16





B308 Safety Tamper Proof Gun - Tip swivels to prevent removal. Excellent General Purpose Blow Gun.



B306 Standard Safety Gun - Draws additional air through slots in tip to increase output flow by 40%.



B307 Strata Flo Gun - High velocity - concentrates air into a less turbulent stream for quieter operation.

#### **TIPS & ACCESSORIES**

These Tips can be placed on any INTERSTATE B300 or B500 Series Blow Gun Body to produce a Blow Gun that meets OSHA 1910.242b and 1910.95.

\$1.95 EA

BT1 BT2 **Brass Tip Rubber Tip** for B300 & B301 for B300 & B302



\$4.36 EA

\$4.95 EA

BT6S Standard Safety Tip - used on B306.



\$4.58 EA

\$6.48 EA

BT7S Strata Flow Tip - used on B307.



BXS06 Safety Extension - 6" \$7.96 EA

BXS12 Safety Extension - 12" \$10.98 EA BXS24 Safety Extension - 24" \$18.56 FA BXS36 Safety Extension - 36" \$24.15 EA

\$15.82 EA

\$16.80 EA



B309XS3 Safety Extension Gun - Basic Blow Gun with 3" extension. B309SX6 Safety Extension Gun - Same as B309XS3 with 6" extension.

# **HEAVY DUTYSAFETY BLOW GUNS**

INTERSTATE Heavy Duty Safety Blow Guns have the same safety features as our other safety series blow guns combined with a heavy cast body for durability and long service life in the most rugged applications.

Do not use Blow Guns on air lines that are not regulated, or when pressure at the gun exceeds 150 PSI. Use the correct size male threaded adapter with teflon sealing tape. Make sure gun is securely tightened to the adapter. Adapter must be threaded into the gun for the full depth of the female thread. Do not re-tap or modify thread for a non standard adapter. Use of these products contrary to specifications and directions may result in personal injury or property damage.



B506 Heavy Duty Safety Gun - Draws additional air through slots in tip to increase output flow by 50%.

# TIRE CHUCKS

The Air Line Chucks in this catalog are designed to exacting standards and are compatible with the industry standards for pneumatic applications.

Chucks for "Live Air Line Only" have a built in shut-off valve and will not work on inflator gauges. Chucks for "Inflator Gauges Only" do not have a shut-off valve and will not work on live air lines.



T04 Angled Ball Foot Chuck. Machined brass body, 1/4" NPTF inlet threads, internal shut-off valve - for use on Live Air Lines Only. Fits \$3.90 EA long valve stems.

T34 Same as T04 but without internal shut-off valve - for use on Inflator \$4.50 EA Gauges Only.



T01 Ball Foot Chuck Clip -Converts any Ball Foot Chuck for "Hands Free" use.