

SPOT WELDERS, PORTABLE and 15 KVA PEDESTAL (MANUAL ROCKER ARM)

LENCO introduces the newly designed L-6000 MARK III resistance spot welder. Generating 6,000 amps, it is the only pneumatic squeeze-type welder of its kind that is liquid cooled all the way to the tips - ensuring maximum welding power which produces consistent weld penetration. The L-6000 MARK III has its own self-contained coolant circulator, operator friendly controls, and service cart for easy mobility around the shop. But the features don't stop there; the L-6000 MARK III also includes the ever popular LENCO "dual spot" single side welding cable assembly for areas where access may be a problem, making it absolutely the most complete welder at the most affordable price on the market. So when you are ready to seriously cut time and increase profits, step up to the L-6000 MARK III and make the LENCO advantage yours.

MARK III

Liquid Cooled
"All The Way
To The Tips"

Heavy Duty Steel
Construction
Throughout

Operator
Friendly
Controls

Self Contained
Coolant
Circulator



Part #L-6000
(see table below)

Includes LENCO
"dual spot" Single Side
Weld Cable Assembly

Part #20946
Wheelhouse Electrode
Arms (optional)
Price \$225.00 set



Part #20947
14" Electrode Arms
(optional)
Price \$245.00 set



THE LENCOSPOT® MARK II® Dual-Spot Welder



208/230 V
&
460/480 V

With the LENCOSPOT® MARK II® Welder, you can make factory type spot welds in the shop. It's simple to operate ... simply press the two electrode guns against the work, press the button and the welder does the work. Two spot welds every time. Time of the welds are automatically controlled by solid state electronic circuitry. No guess work ... no gases or wire to buy ... no warpage...no flame ... and perfect welds time after time, panel after panel. It is the perfect answer to lower the ever rising labor costs.

- Protected Control Panel
- Streamlined Construction
- On/Off Indicating Switch
- Solid State Timer
- Tool Storage Space
- Easy Portability
- Converts to a "Pinch Type" with the optional UNI-SPOT III

Part No's. L-4000 & L-4480
(see table below)

Replacement Panel
Tips Part #A-144
Price \$10.80 Pr.

There is no need to disconnect the dual-spot cable assembly when using the UNI-SPOT III attachment with your LENCO spot welder. You will need to connect the trigger switch plug on the attachment you wish to use.

UNI-SPOT III

Attach the "UNI-SPOT III" to your
LENCOSPOT® MARK II® Dual-Spot Welder

- Eliminate warpage
- Eliminate distortion
- Reduce weld clean-up
- Welds two combined pieces of 18 gauge
- Pinch type spot welds



Part No. L-950
Price \$595.00



Long Spot Tip
Part No.
UL-201
Price \$15.95

Short Spot Tip
Part No.
US-202
Price \$13.95

Drip Rail Spot Tip
Part No.
UD-203
Price \$15.95

Part No.	Price	Description	Primary Voltage	KVA Rating	Line Fuse	Size	Power Input Cable	Maximum Welding Capacity	Duty Cycle	Shipping Weight
L-6000	\$3,999.00	LENCO SPOT® MARK III	208/230 Single Phase 60/50 HZ	6	60 Amp	45" H, 16" W, 28" D	50', No. 10/3 Wire	3pcs 20 ga.-Squeeze type 2pcs 20 ga.-Single side	50%	250 lbs.
L-4000	\$1,150.00	LENCO SPOT® MARK II	208/230 Single Phase 60/50 HZ	4	50 Amp	20-1/2" H, 11" W, 16" D	50', No. 10/3 Wire	2pcs 20 ga.-Single side 18 ga. with Uni-Spot III	na	110 lbs.
L-4480	\$1,280.00	LENCO SPOT® MARK II	460/480 Single Phase 60/50 HZ	4	30 Amp	20-1/2" H, 11" W, 16" D	na	2pcs 20 ga.-Single side 18 ga. with Uni-Spot III	na	97 lbs.

na = not available



INDUSTRIAL, PEDESTAL SPOT WELDER, 15 KVA

AP Automation Pedestal Spot Welder

- Solid State controls
- Variable throat depth: 6" - 17 1/4"
- Water-Cooled
- Standard Arms included
- Heavy Duty Chassis
- One Year Warranty
- 50% Duty Cycle
- 230/460 V Single Phase
- Stroke: 2" - 4" (depending on throat depth)

Part No. 57151031

Call for Price

15 KVA FOOT-OPERATED ROCKER ARM 451 lbs.

- **Welding Capacity:**
Sheet Metal 10-gauge to 10-gauge steel
Rod Diameter: 1/2" to 1/2"
- **Input Power: Single Phase**
230V 100 Amp fuse
460V 50 Amp fuse
- **Manual pressure (Max. 270 daN)**

