



H E A V Y - D U T Y

3/4" HEX DEMOLITION HAMMER MODEL 5337-21



Note: To reduce the risk of damage to the bit lock, do not use round hex shank bits, only use hex bits in this tool.

Hard Hitting and Big on Performance

...the best combination of power, performance, comfort and overall ease of use

Brookfield, WI – Milwaukee Electric Tool Corporation introduces the 5337-21 Rotary/ Demolition Hammer with 19.9 ft-lbs of blow energy, an in-line design and user friendly features that make tool use less taxing on the operator. Model 5337-21 is ideal for demolition work, driving ground rods, scraping splatter and adhesives, removing tile, digging in hard or frozen ground, tamping small areas or bushing surfaces before new surface applications.

The 5337-21 3/4" hex demolition hammer offers high blow force for fast demolition. The exclusive Vibration Isolation System and in-line design reduce worker fatigue. It utilizes vibration reducing materials and a floating-action switch handle that cuts vibration to the user. The handle can be mounted left, right or at the rear of the tool to comfortably match the application.

Because this tool is often used on ground-level jobs, when the handle is mounted in the rear position it makes these tools much more comfortable to operate because users don't have to bend or hunch over the tool while breaking or drilling concrete.

Model 5337-21 also has a speed control that matches the tool speed to the job. The electronic feedback control circuit provides soft-start and then maintains tool speed under load.

It is built to last. It has all-metal barrels and gear housings, metal side handles and steel gears and components. The double-insulated construction helps assure safe use in harsh working environments.

Model 5337-21 is built to operate at least 200 hours before needing planned maintenance. Eight hours before the tool reaches this service interval, the service reminder light glows to alert the operator to complete planned maintenance. If the tool reaches 200 hours without servicing, it will shut down until maintenance is completed.

Servicing the tool is easy. Two service panels have large openings for fast brush and grease changes. Plus, there is no guessing which service kit to use - one kit number works on all four models. Service time is reduced by as much as two-thirds from previous models.



A. B. C. D. E. F.	PRICE
A. 48-62-3005	Bull Point 18" \$16.75 EA
B. 48-62-3010	Flat Chisel 1" x 12" \$13.85 EA
C. 48-62-3015	Flat Chisel 1" x 18" \$16.75 EA
D. 48-62-3025	Wood Chisel 2" x 12". \$25.30 EA
E. 48-62-3030	Scaling Chisel 3" x 12" \$22.90 EA
F. 48-62-3040	Clay Spade 4-1/2" x 16" \$53.55 EA

Maintenance Kit #14-46-0041 \$58.90 Ea
 (2) Ball Bearings, (8) M8X40 Screw, (9) M5X16 Screw, Carbon Brush Set, Bearing Cup, Gear Box O'ring, all (16) necessary O'rings, Gear Box Cover Gasket, Felt, Cord Protector, Retaining Ring, (6) Gear Box Cover Washers, (2) Grease "P" 100gr, Grease "Q" 45gr.

Lock-on button continuous operation
On/Off trigger switch
Gear case cover can be quickly and easily removed to service gears, barrels and gear case



Vibration isolating system

Straight side handle, Part Number 43-62-0042, can be mounted on either side of gear case plus rear handle for optimal comfort

Soft grip handle

3/4" Heavy-duty steel bit holder

Bit Lock

Auto-stop brushes protect the motor from burning out

Alternative straight side handle position (both sides)

Spade handle adjusting knob
Patented 360 degree Spade (D) Handle, Part Number 43-62-0043, w/Vibration isolation System and Tactile Soft Grip minimizes vibration and optimizes comfort




Automatic Lubrication System – produces a permanent grease vapor that continuously lubricates.

Electronic Feedback Control Circuit (EFCC) optimizes chipping performance
Soft Start eliminates Bit wandering

Service Reminder Light alerts operator when service is required

Speed control dial

G. H. I.	PRICE
G. 48-62-3070	Ground Rod Driver, 9 3/4" L \$80.15 EA
H. 48-62-3085	1 pc. Bush Tool, 1-3/4" Sq. x 9 3/4" L \$66.55 EA
I. 48-62-3090	Asphalt Cutter 5" x 16-1/2" L \$89.25 EA



\$1,575 EA

IMPORTANT READ OWNERS MANUAL BEFORE USING THIS TOOL

SPECIFICATIONS

ORDER NUMBER	VOLTS AC ONLY	AMPS	BLOWS PER MINUTE	BIT SHANK SIZE	LENGTH	NET WT. LBS.*	SHIPPING WT. LBS.
5337-21	120	14 .0	975 – 1,950	3/4" HEX	27.5"	24.2	45

STANDARD EQUIPMENT: "D" Handle, Straight Handle, and Carrying Case

*Tool with Side Handles